

## **SAFETY DATA SHEET**

# **WANOL F3156**

## WANHUA CHEMICAL GROUP Co., LTD.

Chemwatch Hazard Alert Code: 0

Issue Date: 09/03/2018

Version No: 1.1 Safety Data Sheet Safety Data Sheet - Authored according to GB/T16483(2008) and GB/T17519(2013)

Print Date: **09/03/2018**L.GHS.CHN.EN

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	WANOL F3156
Synonyms	Polyether polyol WANOL F3156
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses A block foam material for high, medium and low density soft polyurethane; It can also be used to synthesize polyether defoamer.

## Details of the supplier of the safety data sheet

	4
Registered company name	WANHUA CHEMICAL GROUP Co., LTD.
Address	No.17 Tianshan Road, Yantai, Shandong China
Telephone	0535-3031150
Fax	0535-338222-1150
Website	https://www.whchem.com
Email	whsds@whchem.com

## Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	+86 532-83889090
Other emergency telephone numbers	+86 535-8203123

## **SECTION 2 HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

## SUMMARY OF HAZARD IN AN EMERGENCY SITUATION

Liquid.Does not burn.

Classification [1]	Not Applicable

## Label elements

Hazard pictogram(s)	Not Applicable
	NOT APPLICABLE

## Hazard statement(s)

Not Applicable

## Precautionary statement(s) Prevention

Not Applicable

## Precautionary statement(s) Response

Not Applicable

## Precautionary statement(s) Storage

Not Applicable

## Precautionary statement(s) Disposal

Not Applicable

Issue Date: 09/03/2018 Print Date: 09/03/2018

## **Physical and Chemical Hazard**

Liquid.Does not burn.

## **Health Hazards**

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models).  Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Еуе	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

#### **Environmental Hazards**

See Section 12

#### Other hazards

#### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
9082-00-2*	100	Glyercol propoxylated-b-ethoxylated

## **SECTION 4 FIRST AID MEASURES**

## Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  ► Flush skin and hair with running water (and soap if available).  ► Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

# Advise for rescue team (PPE requirement for rescue personnel)

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5 FIREFIGHTING MEASURES**

## **Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

## Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.	
Advice for firefighters		
Fire Fighting	<ul> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>Do not approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>	
Fire/Explosion Hazard	► Non combustible.  ► Not considered a significant fire risk, however containers may burn	

▶ Not considered a significant fire risk, however containers may burn.

WANOL F3156

Issue Date: **09/03/2018**Print Date: **09/03/2018** 

## **SECTION 6 ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

See section 8

## **Measures for Preventing Secondary Contamination**

Refer to section above

## **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>Wipe up.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Prevent spillage from entering drains, sewers or water courses.</li> <li>Recover product wherever possible.</li> <li>Put residues in labelled containers for disposal.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 HANDLING AND STORAGE**

#### Precautions for safe handling

Precautions for safe handling	
Safe handling	<ul> <li>Limit all unnecessary personal contact.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Other information	

# Conditions for safe storage, including any incompatibilities

Suitable container	Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed.  None known

## **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

## Control parameters

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Not Available

#### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Glyercol propoxylated-	Polyglycol 15-200; (Oxirane, 2-methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1); Calthane NF and ND "B")	30	330	2,000
b-ethoxylated		mg/m3	mg/m3	mg/m3

Ingredient	Original IDLH	Revised IDLH
Glyercol propoxylated- b-ethoxylated	Not Available	Not Available

## MATERIAL DATA

# **Exposure controls**

Appropriate engineering	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be
controls	highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Chemwatch: 9-519062 Version No: 1.1

WANOL F3156

# Page 4 of 7 Issue Date: 09/03/2018 Print Date: 09/03/2018

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

## Personal protection







- Safety glasses with side shields
  - ▶ Chemical goggles.

## Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NIZS 1336 or national equivalent]

#### Skin protection

See Hand protection below

Wear general protective gloves, eg. light weight rubber gloves.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

 $Suitability \ and \ durability \ of \ glove \ type \ is \ dependent \ on \ usage. \ Important factors \ in \ the \ selection \ of \ gloves \ include:$ 

- frequency and duration of contact,
- · chemical resistance of glove material,
- · glove thickness and
- dexterity

# Hands/feet protection

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- · Contaminated gloves should be replaced.

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

Issue Date: **09/03/2018**Print Date: **09/03/2018** 

## **WANOL F3156**

	•
	<ul> <li>Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> <li>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</li> </ul>
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities.  OTHERWISE:  Overalls.  Barrier cream.  Eyewash unit.
Thermal hazards	Not Available

## **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

	ı				
Appearance	No suspended matter, no mechanical impurities uniform viscous liquid.				
Physical state	Liquid	Relative density (Water = 1)	1.02		
Odour	Odourless	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available		
pH (as supplied)	5-7	Decomposition temperature	Not Available		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	450-600		
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available		
Flash point (°C)	Not Available	Taste	Not Available		
Evaporation rate	Not Available	Explosive properties	Not Available		
Flammability	Not Available	Oxidising properties	Not Available		
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available		
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available		
Vapour pressure (kPa)	Not Available	Gas group	Not Available		
Solubility in water (g/L)	Not Available	pH as a solution (1%)	Not Available		
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available		

# SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## **SECTION 11 TOXICOLOGICAL INFORMATION**

WANOL F3156			RITATION ot Available		
Glyercol propoxylated- b-ethoxylated	TOXICITY  Oral (rat) LD50: 2037 mg/kg <sup>[1]</sup>			IRRITATION  Not Available	
Legend:	Value obtained from Europe ECHA Registered Substated at a extracted from RTECS - Register of Toxic Effect of control of the second		Value obtained from n	nanufacturer's SDS. Unless otherwise specified	
Legend: Acute Toxicity		chemical Substances	Value obtained from n	nanufacturer's SDS. Unless otherwise specified	
	data extracted from RTECS - Register of Toxic Effect of c	chemical Substances		nanufacturer's SDS. Unless otherwise specified	
Acute Toxicity	data extracted from RTECS - Register of Toxic Effect of c	chemical Substances  Car  Rel	rcinogenicity	nanufacturer's SDS. Unless otherwise specified	
Acute Toxicity Skin Irritation/Corrosion	data extracted from RTECS - Register of Toxic Effect of c	chemical Substances  Car  Rel	rcinogenicity opportunity oppo	nanufacturer's SDS. Unless otherwise specified	

Page 6 of 7 **WANOL F3156**  Issue Date: 09/03/2018 Print Date: 09/03/2018

Legena:

A − Data available but does not fill the criteria for classification
 Y − Data available to make also fill the criteria.

Data Not Available to make classification

#### **SECTION 12 ECOLOGICAL INFORMATION**

#### Toxicity

WANOL F3156	ENDPOINT  Not Available	TEST DURATION (HR)  Not Available	SPECIES  Not Available	VALUE Not Available	SOURCE Not Available
Glyercol propoxylated- b-ethoxylated	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
b-etiloxylateu	Not Available	Not Available	Not Available	Not Available	Not Available

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

## **Bioaccumulative potential**

Ingredient	Bioaccumulation
	No Data available for all ingredients

#### Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

#### Other adverse effects

No data available

## **SECTION 13 DISPOSAL CONSIDERATIONS**

## Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- Waste chemicals: ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
  - It may be necessary to collect all wash water for treatment before disposal.
  - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
  - Where in doubt contact the responsible authority.
  - ▶ Recycle wherever possible.
  - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
  - ▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).
  - ▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Contaminated packing materials:

Refer to section above

**Precautions for Transport:** Refer to section above

# **SECTION 14 TRANSPORT INFORMATION**

#### Labels Required

Marine Pollutant	NC

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# Page 7 of 7 **WANOL F3156**

Issue Date: 09/03/2018 Print Date: 09/03/2018

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

**Precautions for Transport** 

**Suitable Containers** 

See section 7

#### **SECTION 15 REGULATORY INFORMATION**

Safety, health and environmental regulations / legislation specific for the substance or mixture

GLYERCOL PROPOXYLATED-B-ETHOXYLATED(9082-00-2\*) IS FOUND ON THE FOLLOWING REGULATORY LISTS

China Inventory of Existing Chemical Substances

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	N (Glyercol propoxylated-b-ethoxylated)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	N (Glyercol propoxylated-b-ethoxylated)
Japan - ENCS	N (Glyercol propoxylated-b-ethoxylated)
Korea - KECI	Υ
New Zealand - NZIoC	Y
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

#### **SECTION 16 OTHER INFORMATION**

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## **Definitions and abbreviations**

PC – TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$ 

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

# Disclaimer

The information in the SDS applies only for the specified product and does not include mixtures of this product with other substances and mixtures. The SDS provides product safety information for personnel trainned to use this product only.

Powered by AuthorITe, from Chemwatch.